


Close Hook-Up "CH" Style LG

- Close Hook-up design insures the longest possible glass length for a given vessel C-C
- LG chamber elongated to accomodate lateral ports
- Gage valves can be set closer together than a standard end connected gage, within 3/8" of the visible glass dimension, see Table
- Permits use of spherical unions

Irregularities in parallelism of upper & lower vessel nozzles can cause the vessel unions to be out of square. The two point attachment of a typical sight glass requires simultaneous squareness when making up the unions - otherwise leak at the union or excessive strain of the connector and the "connecting nipples" will result

Spherical Union Advantages:

- Minimize piping strain
- Minimize leak at union
- 1.7x stronger in bending than regular Flat Floating Union vessel connector.... more suitable for long and heavy gages



Angular misalignment often seen on horizontal vessels and field constructed piping

Corrected with use of spherical unions - as shown

Reference Documents: EN.RT-D5, Eng. Notes M991980, MOC

General Arrangement Drawing Level Gage & Gage Valve Combo

Transparent Style: T100 / T200 Level Gage, Side Connected Gage Valves, Double Union: FT25 Assembly Orientation: Fig. 5-3-R Offsets Inside

All dimensions in Inches

Inferno Manufacturing Corporation

115 Ricou St. Shreveport, LA USA 71107
T (318) 221-8454 F (318) 222-4106

<http://www.infernomfg.com/>

inferno@infernomfg.com

Drawing No: **GA.TD5-3-R**


Drawing Date: 10/11/2019

Revision: 0

Rev Date: N/A

© 2019 Inferno Mfg Corp

Sheet: 1/4



Example 1: T100-19 CH (32#) ... use 1/2 NPS connecting nipples

Case A, Typical arrangement: mounted on 14" vessel centers ...
 $D = (14 - 12.625 \text{ vis. glass}) / 2 = .687"$

Case B, Factory minimum - Catalog standard: design vessel nozzles at 12.625" C-C, to match the visible glass length ...
 $D = 0$

Example 2: T100-89 CH (256#) ... use 3/4 NPS connecting nipples


Case A, Typical arrangement: mounted on 114" vessel centers ...
 $D = (114 - 111.5 \text{ vis. glass}) / 2 = 1.25"$

Case B, Factory minimum - Catalog standard: design vessel nozzles at 111.875" C-C (111.5 + .375), to "match" the visible glass length ...
 $D = .187"$


Table - Ref. Fig. 5-3

Gage Port NPS	Minimum Vessel C-C Equals	D = distance from lower glass view to lower vessel C/L	Min. D	Min. Gage Port C-C	E = distance from lower glass view to lower gage port	F
1/2	Visible Glass	(Vessel C-C minus Visible Glass / 2)...or specify asymmetry if required	0	Visible Glass + 1.5"	Min. .75"	1.5"
3/4	Visible Glass + .375"		.187"	Visible Glass + 1.875"	Min. 1.062"	2"


Offsets Inside




Offsets Outside



Offsets Parallel



Special Side / End Connected



General Arrangement Drawing
 Level Gage & Gage Valve Combo

Transparent Style: T100 / T200
 Level Gage, Side Connected
 Gage Valves, Double Union: FT25
 Assembly Orientation: Fig. 5-3-R
 Offsets Inside

All dimensions in Inches

Inferno Manufacturing Corporation
 115 Ricou St. Shreveport, LA USA 71107
 T (318) 221-8454 F (318) 222-4106

<http://www.infernomfg.com/>

inferno@infernomfg.com

Drawing No: **GA.TD5-3-R**

Drawing Date: 10/11/2019

Revision: 0

Rev Date: N/A

© 2019 Inferno Mfg Corp


Sheet: 2/4

Choice of Vessel Union Connector

3/8" inside diameter flow path

FLAT / FLOATING UNION


Linear Adjustment



Permits up to 1/4" on vessel centers (pair)


SPHERICAL UNION

Angular Adjustment




Larger section modulus "Z" than FLAT floating union connector, 1.7x stronger in bending


Recommended for angular misalignment due to non-jig set construction, vibration service, & long / heavy gages




Soft Seal: Static O'ring
Standard feature



Union Nut omitted for clarity



Primary Seal: Metal to Metal
O'ring not required



General Arrangement Drawing
Level Gage & Gage Valve Combo

Transparent Style: T100 / T200
Level Gage, Side Connected
Gage Valves, Double Union: FT25
Assembly Orientation: Fig. 5-3-R
Offsets Inside

All dimensions in Inches

Inferno Manufacturing Corporation

115 Ricou St. Shreveport, LA USA 71107
T (318) 221-8454 F (318) 222-4106

<http://www.infernomfg.com/>

inferno@infernomfg.com

Drawing No: **GA.TD5-3-R**

Drawing Date: 10/11/2019

Revision: 0

Rev Date: N/A


© 2019 Inferno Mfg Corp

Sheet: 3/4

Center to Center Adjustment using Spherical Unions




Vessel connectors remain parallel after rotation



If required, use a soft hammer to "bump" the spherical union vessel connector into "rotated" position.

Note: the horizontal connecting axis between LG and GV permits use of spherical union, which will overcome both angular AND vessel C-C misalignment at the same time.

Gage Port Options



Design vessel C-C distance using Table 1... where
Vessel C-C = Visible Glass (1/2 NPS), or
Vessel C-C = Visible Glass + .375" (3/4 NPS)

Factory customized to match
vessel centers

General Arrangement Drawing
Level Gage & Gage Valve Combo

Transparent Style: T100 / T200
Level Gage, Side Connected
Gage Valves, Double Union: FT25
Assembly Orientation: Fig. 5-3-R
Offsets Inside

All dimensions in Inches

Inferno Manufacturing Corporation

115 Ricou St. Shreveport, LA USA 71107
T (318) 221-8454 F (318) 222-4106

<http://www.infernomfg.com/>

inferno@infernomfg.com

Drawing No: **GA.TD5-3-R**

Drawing Date: 10/11/2019

Revision: 0

Rev Date: N/A

© 2019 Inferno Mfg Corp

Sheet: 4/4