Gage Column Model Numbering System (9 Letter)

R 100 _ 1 7 A A N A A B C A A

Pressure/Type	Reflex Series	Transparent Series	Gage Series
Standard- Bar Stock	RA	TA	
Mid Pressure	R100, RDM	T100, TDM	
High Pressure	R200, RDH	T200, TDH	

1 thru 10	# Sections
1 thru 9	Glass Size

Ends Only (Top & Bottom) - 2 Ports	**A**	Connection Position
Side & Ends - 4 Ports (C-C required)	B	
Back & Ends - 4 Ports (C-C required)	C	**(A = Standard)**

1/2" NPT Female	**A**	
3/4" NPT Female	B	
1/8" NPT Female	C	
1/4" NPT Female	D	
3/8" NPT Female	E	
1/2" 150# RF ANSI	F	
1/2" 300# RF ANSI	G	
1/2" 600# RF ANSI	H	
3/4" 150# RF ANSI	J	
3/4"-300# RF ANSI	K	
3/4"-600# RF ANSI	L	
1"-150# RF ANSI	M	End Connection
No End Connections	N	
1/2" Socket Weld	O	**(A = Standard)**
1"-300# RF ANSI	P	
1"-600# RF ANSI	Q	
1-1/2"-150# RF ANSI	R	
1-1/2"-300# RF ANSI	S	
1-1/2"-600# RF ANSI	T	
3/4" Socket Weld	V	
2"-150# RF ANSI	W	
Other	X	
2"-300# RF ANSI	Y	
2"-600# RF ANSI	Z	

1/2" NPT Female	A	
3/4" NPT Female	B	
1/8" NPT Female	C	
1/4" NPT Female	D	
3/8" NPT Female	E	
1/2" 150# RF ANSI	F	
1/2" 300# RF ANSI	G	
1/2" 600# RF ANSI	H	
3/4" 150# RF ANSI	J	
3/4"-300# RF ANSI	K	
3/4"-600# RF ANSI	L	
1"-150# RF ANSI	M	Side/Back Connections
No Side Connection	**N**	
1/2" Socket Weld	O	**(N = Standard)**
1"-300# RF ANSI	P	
1"-600# RF ANSI	Q	
1-1/2"-150# RF ANSI	R	
1-1/2"-300# RF ANSI	S	
1-1/2"-600# RF ANSI	T	
3/4" Socket Weld	V	
2"-150# RF ANSI	W	
Other	X	
2"-300# RF ANSI	Y	

Revision C
Rev. Date: 4-20-12
INFERNO MFG CORP

Accessories (**A = Standard**)

A	**No Accessory**
B	Mica Shield
C	Kel-F™ Shield
E	Scale
F	Non-Frost Extension
G	Explosion-Proof Illuminator
H	External Heating Chamber (Rear)
J	External Heating Chamber (Dual)
K	Internal Heating Tube/Fittings
L	Belleville Spring Washers
M	Mirrors, safety side viewing
N	Internal ball float, enhanced interface - See Thru
X	Other

Nut/Bolt Material (**A = Standard**)

A	**A-194 2H / A-193 B7**
C	Steel per NACE / A-193 B7M GAGE IS DE-RATED
D	A-194 Gr8 / A-193 B8 Cl 2 (304 SS)
E	A-194 Gr8M / A-193 B8M Cl 2 (316 SS)
H	Alloy 20 / Alloy 20
J	Monel 400 / Monel 400
X	Other

Gasket Seal / (Cushion) (**C = Standard**)

A	~~NON-asbestos (NBR) / Same~~ *Now using Grafoil*
P	Gylon 3504™ Premium TFE/ NON-asbestos
C	**Grafoil™ w SS insert/ NON-asbestos** (Oilfield & Steam)
X	Other / Other

Glass Material (**B = Standard**)

A	Aluminosilicate, Tempered
B	**Borosilicate, Tempered**
X	Other

Cover Flange Material (**A = Standard**)

A	**ASTM A216 WCC or AISI 1018 Steel**
B	ASTM A216 WCC, or AISI 1018 per NACE MR-01-75
D	T-304 Stainless Steel
E	T-316 Stainless Steel
H	Alloy 20 (Carpenter 20™)
J	Monel 400
K	C-276 (Hastelloy C-276™)
L	AISI 4130 Quenched & Tempered
M	AISI 4140 Quenched & Tempered
X	Other

Body Material (Wetted Parts) (**A = Standard**)

A	**ASTM A216 WCC, AISI 1018 NACE MR-01-75**
B	ASTM A216 WCC, or AISI 1018 per NACE MR-01-75
D	T-304 Stainless Steel
E	T-316 Stainless Steel
H	Alloy 20 (Carpenter 20™)
J	Monel 400
K	C-276 (Hastelloy C-276™)
L	AISI 4130 Quenched & Tempered
M	AISI 4140 Quenched & Tempered
X	Other